


Stainless Steel Braided Galvanised Steel Conduits - Type ASLB

These conduits provide mechanical and EMC protection in critical applications. This robust, stainless steel braid cover provides a high level of electromagnetic shielding for cables. Typical applications include the steel, foundry, metalworking and other demanding heavy-duty industries.

Technical Data

Colour	Metal
Temperature Range	-55° C to +300° C
Protection Class	IP 40
Tensile Strength	Heavy (1000 N)
Impact Strength	Heavy (6 J)
Compression Ressitance	Heavy (1250 N)
Construction	Galvanized Steel, Square-Locked Core with Stainless Steel Braid (AISI 304)

Accessories

Image	Cat. no.	Description
	P Type Mounting Clips	'P' type mounting clips are ideal elements for retaining /...

Approvals

RoHS

Product Drawing



Square locked profile
with galvanized
steel brading

Ordering Information

Cat. No.	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius R (mm)	Size	Standard Pack (meters)
ASLB-3/8"	12.6	15.8	45	3/8"	30
ASLB-1/2"	16	20.5	55	1/2"	30
ASLB-3/4"	21	25.5	70	3/4"	30
ASLB-1"	26.5	32.8	95	1"	30
ASLB-1 1/4"	35.1	40.5	115	1 1/4"	30
ASLB-1 1/2"	40.3	46.5	165	1 1/2"	30
ASLB-2"	51.6	58	210	2"	30