


CONUS CABLE GLANDS



These economical screw type glands are used for securing round cables in normal applications. They are also available for securing flat cables on request.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7035 (Light Grey)
Protection Class	IP 54
Sealing Ring	TPE
Pressure Washer	Poly Propylene (PP)
Temperature Range	-20 ^o C to +80 ^o C Continuous +150 ^o C Intermittent
Threads available	Pg - DIN 40430

Size	Cat. No. Round Cables	Cat. No. Flat Cables	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm) Round Cables	Size of Flat Cables (mm)	Standard Pack (pieces)
Pg 7	BD-11	BDF-11	12.5	8	15	3 - 6	-	100
Pg 9	BD-12	BDF-12	15.2	8	19	4.5 - 7	-	100
Pg 11	BD-13	BDF-13	18.6	8	22	6 - 9	-	100
Pg 13.5	BD-14	BDF-14	20.4	9	24	9 - 12	-	100
Pg 16	BD-15	BDF-15	22.5	10	27	11 - 14	-	100
Pg 21	BD-16	BDF-16	28.3	11	33	14 - 18	10 x 3.2	50
Pg 29	BD-17	BDF-17	37	11	42	18 - 25	15 x 4.4	25
Pg 36	BD-18	BDF-18	47	13	53	25 - 32	25 x 4.6	20