



Junction Box with Knockouts

Junction Boxes with knockouts are made of halogen-free ABS, which has high resistance to chemicals and atmospheric agents. These knockouts can be easily cut out in a wide range of diameters allowing for a selection of cable gland size as per cable diameter. By virtue of the design they offer IP 65 protection with the help of silicon rubber gasket in EPDM. They are available with plain walls, nipples and membrane. Junction-Box are offered with press-on lids, screw lids and hinged lids.

Stainless steel screws are also available on request for lid fastening. Choice of grey colour lid or transparent lid is also available on request.

Technical Data

Material	Thermoplastic
Colour	Grey
Temperature Range	-25° C to +60° C
Protection Class	IP 67
Screw	Zinc Plated and Chromate passivated
Gasket	Silicon Rubber EPDM
Lid	Grey Colour / Transparent
Standard	IEC 670, CEI 23-48

Approvals



Ordering Information

Grey Screwed Lid

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Knockouts	Standard Pack
T2056M	90	90	50	4	1
T2066M	100	100	50	8	1
T2136M	110	110	65	8	1
T1505M	150	110	70	10	1
T2146M	210	110	70	12	1
T2176M	210	140	90	12	1
T5005M	210	210	90	12	1
T8005M	240	190	90	12	1
T2156M	290	210	90	14	1
T7005M	290	290	90	16	1

Transparent Screwed Lid

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Knockouts	Standard Pack
T1507M	150	110	70	10	1
T2141M	210	110	70	12	1
T2171M	210	140	90	12	1
T5007M	210	210	90	12	1
T8007M	240	190	90	12	1
T7007M	290	290	90	16	1

Grey Screwed High Top Lid

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Knockouts	Standard Pack
T1605M	150	110	120	10	1
T2205M	210	110	120	12	1
T2186	220	130	140	12	1
T5205M	210	210	140	12	1
T8205M	240	190	160	12	1
T2226M	290	210	140	14	1
T7205M	290	290	140	16	1

Transparent Screwed High Top Lid

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Knockouts	Standard Pack
T1207M	110	110	100	8	1
T1607M	150	110	120	10	1
T2207M	210	110	120	12	1
T5207M	210	210	140	12	1
T8207M	240	190	160	12	1
T7207M	290	290	140	16	1