







These Glands offer maximum protection against conductor fatigue caused by flexing cables. Designed for kink protection and mainly used for moving machine assemblies. They are available with reduced clamping range also.

Technical Details :	
Material	Polyamide 6
Flammability	UL 94 V2
Colour	RAL 7001 (Grey), RAL 9005 (Black)
Protection Class	IP 68-5 Bar
Sealing Ring	CR-Chloroprene
Temperature Range	-20° C to +100° C Continuous, -30° C to +150° C Intermittent
Attachment Threads	Pg - DIN 40430 Metric - EN 60423 NPT & PF (Available on request)
Approvals	   

SPIRAL CABLE GLANDS



Pg Thread

Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Wrench (mm)	Clamping Range (mm)	Standard Pack (pieces)
Pg 7	BSSP-01	BSSP-21	12.5	8	15	3 - 6.5	100
Pg 9	BSSP-02	BSSP-22	15.2	8	19	4 - 8	50
Pg 11	BSSP-03	BSSP-23	18.6	8	22	5 - 10	50
Pg 13.5	BSSP-04	BSSP-24	20.4	9	24	6 - 12	50
Pg 16	BSSP-05	BSSP-25	22.5	10	27	10 - 14	50
Pg 21	BSSP-06	BSSP-26	28.3	11	33	13 - 18	25

Metric Thread

Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Wrench (mm)	Clamping Range (mm)	Standard Pack (pieces)
M 12 x 1.5	BMSP-0S	BMSP-2S	12	8	15	3 - 6.5	50
M 16 x 1.5	BMSP-01	BMSP-21	16	10	22	5 - 10	50
M 20 x 1.5	BMSP-02	BMSP-22	20	10	24	6 - 12	20
M 20 x 1.5	BMSP-03	BMSP-23	20	10	27	10 - 14	20
M 25 x 1.5	BMSP-05	BMSP-25	25	10	33	13 - 18	20