


STRAIGHT CONNECTORS WITH FLANGE




These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection. These connectors are available with mounting holes for fixing on the panel or equipment surface.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67



For TNOC-12/16



For TNOC-22/28/36/48


Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (pieces)
12	TNOC-12G	TNOC-12B	-	36.5	5.5	45	32	50
16	TNOC-16G	TNOC-16B	-	36.5	5.5	45	32	50
22	TNOC-22G	TNOC-22B	30.5	53.5	6.5	66.5	45	30
28	TNOC-28G	TNOC-28B	30.5	53.5	6.5	66.5	45	20
36	TNOC-36G	TNOC-36B	30.5	72.5	6.5	85.5	64	10
48	TNOC-48G	TNOC-48B	30.5	72.5	6.5	85.5	78	10

STRAIGHT CONNECTORS WITH FLANGE



These connectors are used to clamp standard corrugated conduits. They offer IP67 protection. These connectors are available with mounting holes for fixing on the panel or equipment surface.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67



For TNOC-56/70/95

Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (pieces)
56	TNOC-56G	TNOC-56B	61	67	7	81	96	10
70	TNOC-70G	TNOC-70B	78	84	7	98	113	10
95	TNOC-95G	TNOC-95B	94	108	8	125	146	10