



### Straight & 90° Elbow Glands for ANMSF Conduits - Metric Thread

These fittings are designed for use with conduit types ANMSF. When used in combination with one of these conduits an IP 67 leak-tight cable protection system with a strong pull strength is achieved. They are available in sizes from M16 to M32 in both straight and 90° fashion

### Technical Data

Material	Polyamide PA-6, V-2 , halogenfree
Colour	Grey
Temperature Range	-40° C to +120° C Continuous
Threads available	Metric
Protection Class	IP 67(Dust proof, Water tight)
Construction	Plastic fitting, consisting of 2 parts (counter nut and body)

### Approvals



### Ordering Information

#### Liquid Tight Straight Conduit Glands (Metric Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
BBFM-02A	M16 X 1.5	3/8"	16	14	10.9	25
BBFM-03A	M20 X 1.5	1/2"	20	14	14.4	25
BBFM-04A	M25 X 1.5	3/4"	25	14	18	10
BBFM-05A	M32 X 1.5	1"	32	16	23.9	5
BBFM-06A	M40 X 1.5	1 1/4"	40	16	31.8	5

#### Liquid Tight 90° Conduit Glands (Metric Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
BBFM-02A 90	M16 X 1.5	3/8"	16	14	10.9	10
BBFM-03A 90	M20 X 1.5	1/2"	20	14	14.4	10
BBFM-04A 90	M25 X 1.5	3/4"	25	14	18	10
BBFM-05A 90	M32 X 1.5	1"	32	16	23.9	5