



Junction Box with Smooth Walls

Junction Boxes are made of halogen-free thermoplastic, which has high resistance to chemicals and atmospheric agents. By virtue of the design they offer IP 65 protection with the help of silicon rubber gasket in EPDM. They are available with plain walls, knockouts, nipples and membrane. Junction-Boxes are offered with press-on lids, screw lids and hinged lids. Stainlesssteel screws are also available on request for lid fastening. Choice of grey colour lid or transparent lid is also available on request.

Technical Data

Material	Thermoplastic
Colour	Grey
Temperature Range	-25° C to +60° C
Protection Class	IP 65
Screw	Stainless Steel / Nylon
Gasket	Silicon Rubber EPDM
Lid	Grey Colour / Transparent
Standard	IEC 670, CEI 23-48

Approvals



Ordering Information

Transparent High Top cover with Stainless Steel screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M015.CA.K	460	380	182	1
M011.CA.K	240	190	170	1
M014.CA.K	376	300	180	1
M009.CA.K	190	145	135	1
M010.CA.K	240	190	155	1

Grey cover with Stainless Steel Screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M003.PL	80	80	40	1
M005.PL	100	100	50	1
M006.PL	100	100	70	1
M007.PL	123	75	51	1
M007.X.PL	110	80	60	1
M008.PL	150	110	70	1
M010.PL	243	190	90	1
M009.PL	190	145	72	1
M011.PL	243	190	110	1

Transparent cover with Stainless Steel Screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M009.PK	190	145	72	1
M008.PK	150	110	70	1
M011.PK	243	190	110	1

Grey cover with Nylon Screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M009.A.PL	190	140	75	1
M010.A.PL	238	190	90	1
M012.A.PL	300	220	120	1
T2356(H)	360	250	150	1
M014.A.PL	376	300	120	1
M015.A.PL	456	380	121	1

Transparent cover with Nylon Screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M009.A.PK	190	140	75	1
M010.A.PK	238	190	90	1
M012.A.PK	300	220	120	1
T2366(H)	360	250	150	1
M014.A.PK	376	300	120	1

High Top cover with Stainless Steel screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	Standard Pack
M008.CA.G	150	110	135	1
M009.CA.G	190	145	135	1
M010.CA.G	243	190	155	1
M011.CA.G	243	190	170	1
M012.CA.G	310	230	160	1
M014.CA.G	376	300	180	1
M015.CA.G	460	380	182	1