



Junction Box with Membranes & Nipples

Specially designed and moulded Membranes in these Junction Boxes, act as a Cable Glands offering IP 65 protection. After piercing the membrane with a sharp instrument, the cable / flexible conduit has to be inserted and slightly pulled out (withdrawn) to achieve a tight wrap around the cable / conduit resulting in positive clamping. Junction Boxes are also available with specially designed Nipples which act as Cable Glands offering IP 65 protection.

Technical Data

Material	Thermoplastic
Colour	Grey
Protection Class	IP 65
Screw	Stainless Steel / Nylon
Gasket	Silicon Rubber EPDM
Lid	Grey Colour / Transparent
Standard	IEC 670, CEI 23-48

Approvals



Ordering Information

Junction Boxes with Membrane - Grey cover

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Membranes	Standard Pack
M005CV	94	94	50	10 + 2	1
M008PG	150	110	70	10	1
M009PG	190	145	70	10	1
M011PG	243	190	110	12	1

Junction Boxes with Nipples - Grey cover with stainless steel screw

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Nipples	Standard Pack
M003	80	80	40	6	1
M005	100	100	50	6	1
M006	100	100	70	6	1
M007	123	75	51	6	1
M008	150	110	70	10	1
M009	190	145	72	10	1
M010	243	190	90	12	1
M011	243	190	110	12	1

Junction Boxes with Nipples - Grey cover with nylon hinged screws

Cat. No.	Length (mm)	Width (mm)	Height (mm)	No. of Nipples	Standard Pack
M009.A	190	140	75	10	1
M010.A	238	190	90	12	1
M012.A	300	220	120	12	1
M014.A	376	300	120	12	1
M015.A	456	380	120	14	1