



Male Crimp Contacts

These male crimp contacts are available in 10 Amp and 16 Amp versions. The 10 Amp crimp contacts are suitable for conductor size up to 2.5 sq.mm.and the 16 Amp crimp contact are suitable for conductor size up to 4 sq.mm to be used along with male contact careers.

Technical Data

| | |
|------------------|----------------------------------|
| Material | Turned / Machined Copper Alloy |
| Surface Material | Hard Silver Hard Gold on request |
| Current Capacity | 10 A, 16 A & 40 A |

Accessories

| Image | Cat. no. | Description |
|-------|----------------|--|
| | Crimping Tools | Crimping tools are the basic instruments that are used to... |

Ordering Information

Male Crimp Contacts - Turned

| Cat. No. | Wire Size sq.mm | Current Capacity Amp | Stripping Length | Standard Pack (Pieces) |
|--------------|-----------------|----------------------|------------------|------------------------|
| WMCT0.5/10A | 0.5 | 10 | 8 | 100 |
| WMCT0.75/10A | 0.75 | 10 | 8 | 100 |
| WMCT1.0/10A | 1 | 10 | 8 | 100 |
| WMCT1.5/10A | 1.5 | 10 | 8 | 100 |
| WMCT2.5/10A | 2.5 | 10 | 6 | 100 |
| WMCT0.37/16A | 0.37 | 16 | 7.5 | 50 |
| WMCT0.5/16A | 0.5 | 16 | 7.5 | 50 |
| WMCT0.75/16A | 0.75 | 16 | 7.5 | 50 |
| WMCT1.0/16A | 1 | 16 | 7.5 | 50 |
| WMCT1.5/16A | 1.5 | 16 | 7.5 | 50 |
| WMCT2.5/16A | 2.5 | 16 | 7.5 | 50 |
| WMCT4.0/16A | 4 | 16 | 7.5 | 50 |
| WMCT6.0/40A | 4 | 40 | 9.6 | 100 |