



Straight Conduit Gland - NPT Thread

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in NPT ½" to NPT 1" for conduit size 10 to 28

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	NPT
Protection Class	IP 67

Accessories

Image	Cat. no.	Description
	Polyamide Lock Nut	Lorem Ipsum is simply dummy text of the printing and...

Approvals



Ordering Information

NPT Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-N10G	NPT 1/2"	10	21.2	13	50
PNC-N12G	NPT 1/2"	12	21.2	13	50
PNC-N16G	NPT 1/2"	16	21.2	13	50
PNC-N22G	NPT 3/4"	22	26.5	15	30
PNC-N28G	NPT 1"	28	33.2	15	30

NPT Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-N10B	NPT 1/2"	10	21.2	13	50
PNC-N12B	NPT 1/2"	12	21.2	13	50
PNC-N16B	NPT 1/2"	16	21.2	13	50
PNC-N22B	NPT 3/4"	22	26.5	15	30
PNC-N28B	NPT 1"	28	33.2	15	30