



### Straight Conduit Gland - NPT Thread

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in NPT 1/2" to NPT 1" for conduit size 10 to 28

### Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	NPT
Protection Class	IP 67

### Accessories

Image	Cat. no.	Description
	Polyamide Lock Nut	Lorem Ipsum is simply dummy text of the printing and...

### Approvals



### Ordering Information

#### NPT Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-N10G	NPT 1/2"	10	21.2	13	50
PNC-N12G	NPT 1/2"	12	21.2	13	50
PNC-N16G	NPT 1/2"	16	21.2	13	50
PNC-N22G	NPT 3/4"	22	26.5	15	30
PNC-N28G	NPT 1"	28	33.2	15	30

#### NPT Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-N10B	NPT 1/2"	10	21.2	13	50
PNC-N12B	NPT 1/2"	12	21.2	13	50
PNC-N16B	NPT 1/2"	16	21.2	13	50
PNC-N22B	NPT 3/4"	22	26.5	15	30
PNC-N28B	NPT 1"	28	33.2	15	30