




## Straight Conduit Gland - PF Thread

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in G ¼ "to G 2" for conduit size 7 to 48

### Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	PF
Protection Class	IP 67

### Accessories

Image	Cat. no.	Description
	Polyamide Lock Nut	Lorem Ipsum is simply dummy text of the printing and...

### Approvals



## Ordering Information

### PF Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-G07G	G 1/4"	7	13	11	50
PNC-G10G	G 1/2"	10	20.9	13	50
PNC-G12G	G 1/2"	12	20.9	13	50
PNC-G16G	G 1/2"	16	20.9	13	50
PNC-G22G	G 3/4"	22	26.4	15	30
PNC-G28G	G 1"	28	33.2	15	30
PNC-G36G	G 1¼"	36	41.9	19	10
PNC-G42G	G 1¼"	48	47.8	21	10
PNC-G48G	G 2"	48	59.6	21	10

### PF Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PNC-G07B	G 1/4"	7	13	11	50
PNC-G10B	G 1/2"	10	20.9	13	50
PNC-G12B	G 1/2"	12	20.9	13	50
PNC-G16B	G 1/2"	16	20.9	13	50
PNC-G22B	G 3/4"	22	26.4	15	30
PNC-G28B	G 1"	28	33.2	15	30
PNC-G36B	G 1¼"	36	41.9	19	10
PNC-G42B	G 1¼"	48	47.8	21	10
PNC-G48B	G 2"	48	59.6	21	10