



Connector to Secure Cables & Conduits - PG Male Thread

These Connectors to Secure Cable and Conduit are available in male PG 9 to Pg 48 threads for conduit size 10 to 48

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	Pg
Protection Class	IP 67

Ordering Information

PG Male Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Length L (mm)	Clamping Range (mm)	Standard Pack (Pieces)
PNCC-P07G	Pg 7	10	15	3.5 - 6.5	50
PNCC-P09G	Pg 9	10	15	3.5 - 6.5	50
PNCC-P11G	Pg 11	12	15	4 - 8	30
PNCC-P132G	Pg 13.5	12	15	4 - 8	30
PNCC-P13G	Pg 13.5	16	15	7 - 12	30
PNCC-P16G	Pg 16	16	15	7 - 12	30
PNCC-P21G	Pg 21	22	15	12 - 18	30
PNCC-P29G	Pg 29	28	15	18 - 26	15
PNCC-P36G	Pg 36	36	19	22 - 33	15
PNCC-P48G	Pg 48	48	19	30 - 38	10

PG Male Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Length L (mm)	Clamping Range (mm)	Standard Pack (Pieces)
PNCC-P07B	Pg 7	10	15	3.5 - 6.5	50
PNCC-P09B	Pg 9	10	15	3.5 - 6.5	50
PNCC-P11B	Pg 11	12	15	4 - 8	30
PNCC-P132B	Pg 13.5	12	15	4 - 8	30
PNCC-P13B	Pg 13.5	16	15	7 - 12	30
PNCC-P16B	Pg 16	16	15	7 - 12	30
PNCC-P21B	Pg 21	22	15	12 - 18	30
PNCC-P29B	Pg 29	28	15	18 - 26	15
PNCC-P36B	Pg 36	36	19	22 - 33	15
PNCC-P48B	Pg 48	48	19	30 - 38	10