



Connector to Secure Cables & Conduits - UNEF Female Thread

These Connectors to Secure Cable and Conduit are available in UNEF female thread available in size 1/2-28 to 2-18 suitable for conduit size 10 to 36.

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	UNEF
Protection Class	IP 67

Ordering Information

UNEF Female Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Clamping Range (mm)	Inner Thread Length (mm)	Standard Pack (Pieces)
PICC-U1010G	1/2-28	10	3.5-6.5	13	50
PICC-U1210G	5/8-24	10	3.5-6.5	13	30
PICC-U1410G	3/4-20	10	3.5-6.5	13	30
PICC-U1212G	5/8-24	12	4-8	13	30
PICC-U1412G	3/4-20	12	4-8	13	30
PICC-U1812G	1-20	12	4-8	13	30
PICC-U1616G	7/8-20	16	7-12	13	30
PICC-U1816G	1-20	16	7-12	13	30
PICC-U2016G	1 3/16-18	16	7-12	13	30
PICC-U2816G	1 7/16-18	16	7-12	15	30
PICC-U2222G	1 3/16-18	22	12-16	15	30
PICC-U2822G	1 7/16-18	22	12-16	15	30
PICC-U2828G	1 7/16-18	28	18-26	15	20
PICC-U3228G	1 3/4-18	28	18-26	15	10
PICC-U3628G	2-18	28	18-26	15	10
PICC-U3636G	2-18	36	22-33	19	10

UNEF Female Thread

Cat. No. Black	Size	Suitable for Conduit Size	Clamping Range (mm)	Inner Thread Length (mm)	Standard Pack (Pieces)
PICC-U1010B	1/2-28	10	3.5-6.5	13	50
PICC-U1210B	5/8-24	10	3.5-6.5	13	30
PICC-U1410B	3/4-20	10	3.5-6.5	13	30
PICC-U1212B	5/8-24	12	4-8	13	30
PICC-U1412B	3/4-20	12	4-8	13	30
PICC-U1812B	1-20	12	4-8	13	30
PICC-U1616B	7/8-20	16	7-12	13	30
PICC-U1816B	1-20	16	7-12	13	30
PICC-U2016B	1 3/16-18	16	7-12	13	30

UNEF Female Thread

Cat. No. Black	Size	Suitable for Conduit Size	Clamping Range (mm)	Inner Thread Length (mm)	Standard Pack (Pieces)
PICC-U2816B	1 7/16-18	16	7-12	15	30
PICC-U2222B	1 3/16-18	22	12-16	15	30
PICC-U2822B	1 7/16-18	22	12-16	15	30
PICC-U2828B	1 7/16-18	28	18-26	15	20
PICC-U3228B	1 3/4-18	28	18-26	15	10
PICC-U3628B	2-18	28	18-26	15	10
PICC-U3636B	2-18	36	22-33	19	10