



Straight Connector With Female Thread - UNEF Thread

These female thread connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in special UNEF, Pg, Metric and PF thread configuration. These Straight Connectors with female thread are available in size 1/2-28 to 2-18 suitable for conduit size 10 to 36.

Technical Data

Material	Polyamide 6
Colour	Black & Grey
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	UNEF
Protection Class	IP 67

Ordering Information

UNEF Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Inner Thread Length (mm)	Standard Pack (Pieces)
PIC-U1010G	1/2-28	10	10	50
PIC-U1210G	5/8-24	10	10	50
PIC-U1410G	3/4-20	10	10	50
PIC-U1212G	5/8-24	12	10	50
PIC-U1412G	3/4-20	12	10	50
PIC-U1812G	1-20	12	10	50
PIC-U1616G	7/8-20	16	10	50
PIC-U1816G	1-20	16	10	30
PIC-U2016G	1 3/16-18	16	10	30
PIC-U2816G	1 7/16-18	16	10	30
PIC-U2222G	1 3/16-18	22	10	30
PIC-U2822G	1 7/16-18	22	10	30
PIC-U3622G	2-18	22	10	30
PIC-U2828G	1 7/16-18	28	10	30
PIC-U3228G	1 3/4-18	28	10	30
PIC-U3628G	2-18	28	10	30
PIC-U3636G	2-18	36	10	30

UNEF Thread

Cat. No. Black	Size	Suitable for Conduit Size	Inner Thread Length (mm)	Standard Pack (Pieces)
PIC-U1010B	1/2-28	10	10	50
PIC-U1210B	5/8-24	10	10	50
PIC-U1410B	3/4-20	10	10	50
PIC-U1212B	5/8-24	12	10	50
PIC-U1412B	3/4-20	12	10	50
PIC-U1812B	1-20	12	10	50
PIC-U1616B	7/8-20	16	10	50

UNEF Thread

Cat. No. Black	Size	Suitable for Conduit Size	Inner Thread Length (mm)	Standard Pack (Pieces)
PIC-U1816B	1-20	16	10	30
PIC-U2016B	1 3/16-18	16	10	30
PIC-U2816B	1 7/16-18	16	10	30
PIC-U2222B	1 3/16-18	22	10	30
PIC-U2822B	1 7/16-18	22	10	30
PIC-U3622B	2-18	22	10	30
PIC-U2828B	1 7/16-18	28	10	30
PIC-U3228B	1 3/4-18	28	10	30
PIC-U3628B	2-18	28	10	30
PIC-U3636B	2-18	36	10	30