



Straight Connector With Female Thread - PG Thread

These female thread connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in special UNEF, Pg, Metric and PF thread configuration. This Straight Connector with Female thread is available in PG 11 to Pg 21 threads for conduit size 12 to 22

Technical Data

| | |
|-------------------|--|
| Material | Polyamide 6 |
| Colour | Black & Grey |
| Temperature Range | -40° C to +105° C Continuous, +150° C Short Term |
| Threads available | Pg |
| Protection Class | IP 67 |

Ordering Information

Pg Thread

| Cat. No. Grey | Size | Suitable for Conduit Size | Inner Thread Length (mm) | Standard Pack (Pieces) |
|---------------|---------|---------------------------|--------------------------|------------------------|
| PIC-P11G | Pg 11 | 12 | 14 | 50 |
| PIC-P132G | Pg 13.5 | 12 | 14 | 50 |
| PIC-P16G | Pg 16 | 16 | 14 | 30 |
| PIC-P21G | Pg 21 | 22 | 15 | 30 |

Pg Thread

| Cat. No. Black | Size | Suitable for Conduit Size | Inner Thread Length (mm) | Standard Pack (Pieces) |
|----------------|---------|---------------------------|--------------------------|------------------------|
| PIC-P11B | Pg 11 | 12 | 14 | 50 |
| PIC-P132B | Pg 13.5 | 12 | 14 | 50 |
| PIC-P16B | Pg 16 | 16 | 14 | 30 |
| PIC-P21B | Pg 21 | 22 | 15 | 30 |