



Straight Connector With Female Thread - PF Thread

These female thread connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in special UNEF, Pg, Metric and PF thread configuration. These Straight Connector with Female Thread are available in G 1/2" to G2" threads for conduit size 16 to 48

Technical Data

| | |
|-------------------|--|
| Material | Polyamide 6 |
| Colour | Black & Grey |
| Temperature Range | -40° C to +105° C Continuous, +150° C Short Term |
| Threads available | PF |
| Protection Class | IP 67 |

Ordering Information

PF Thread

| Cat. No. Grey | Size | Suitable for Conduit Size | Inner Thread Length (mm) | Standard Pack (Pieces) |
|---------------|--------|---------------------------|--------------------------|------------------------|
| PIPC-G16G | G 1/2" | 16 | 13.8 | 50 |
| PIPC-G22G | G 3/4" | 22 | 15 | 30 |
| PIPC-G28G | G 1" | 28 | 15 | 25 |
| PIPC-G36G | G 1¼" | 36 | 29 | 10 |
| PIPC-G42G | G 1¾" | 48 | 29 | 10 |
| PIPC-G48G | G 2" | 48 | 29 | 10 |

PF Thread

| Cat. No. Black | Size | Suitable for Conduit Size | Inner Thread Length (mm) | Standard Pack (Pieces) |
|----------------|--------|---------------------------|--------------------------|------------------------|
| PIPC-G16B | G 1/2" | 16 | 13.8 | 50 |
| PIPC-G22B | G 3/4" | 22 | 15 | 30 |
| PIPC-G28B | G 1" | 28 | 15 | 25 |
| PIPC-G36B | G 1¼" | 36 | 29 | 10 |
| PIPC-G42B | G 1¾" | 48 | 29 | 10 |
| PIPC-G48B | G 2" | 48 | 29 | 10 |