



Straight Connector With Female Thread - PF Thread

These female thread connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in special UNEF, Pg, Metric and PF thread configuration. These Straight Connector with Female Thread are available in G 1/2" to G2" threads for conduit size 16 to 48

Technical Data

Material	Polyamide 6
Colour	Black & Grey
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	PF
Protection Class	IP 67

Ordering Information

PF Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Inner Thread Length (mm)	Standard Pack (Pieces)
PIPC-G16G	G 1/2"	16	13.8	50
PIPC-G22G	G 3/4"	22	15	30
PIPC-G28G	G 1"	28	15	25
PIPC-G36G	G 1¼"	36	29	10
PIPC-G42G	G 1¾"	48	29	10
PIPC-G48G	G 2"	48	29	10

PF Thread

Cat. No. Black	Size	Suitable for Conduit Size	Inner Thread Length (mm)	Standard Pack (Pieces)
PIPC-G16B	G 1/2"	16	13.8	50
PIPC-G22B	G 3/4"	22	15	30
PIPC-G28B	G 1"	28	15	25
PIPC-G36B	G 1¼"	36	29	10
PIPC-G42B	G 1¾"	48	29	10
PIPC-G48B	G 2"	48	29	10