



### 90° Conduit Glands - Metric Thread

These 90 Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

### Technical Data

Material	Nickel Plated Brass
Temperature Range	-45° C to +105° C
Threads available	Metric - Red Insert
Protection Class	IP 67

### Accessories

Image	Cat. no.	Description
	Brass / SS Standard Locknuts - Metric Threads	In certain applications, installing cable glands directly on enclosure or...

### Approvals



### Ordering Information

#### Liquid Tight 90° Conduits (Metric Thread)

Cat. No.	Size	Suitable for Conduit Size	Internal Diameter (mm)	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
BBFM-02(S)-90	M 16 x 1.5	5/16"	10.2	16	11.5	50
BBFM-02-90	M 16 x 1.5	3/8"	8.3	16	11.5	50
BBFM-03(S)-90	M 20 x 1.5	3/8"	10.2	20	13	50
BBFM-03-90	M 20 x 1.5	1/2"	13.9	20	13	50
BBFM-04-90	M 25 x 1.5	3/4"	18.5	25	15	25
BBFM-05-90	M 32 x 1.5	1"	23.8	32	15	10
BBFM-06-90	M 40 x 1.5	1 1/4"	31.8	40	15	5
BBFM-07-90	M 50 x 1.5	1 1/2"	36.8	50	18	5
BBFM-08-90	M 63 x 1.5	2"	47.8	63	20	4