



45° Conduit Glands - Metric Thread

These 45 Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

Technical Data

| | |
|-------------------|---------------------|
| Material | Nickel Plated Brass |
| Temperature Range | -45° C to +105° C |
| Threads available | Metric - Red Insert |
| Protection Class | IP 67 |

Accessories

| Image | Cat. no. | Description |
|-------|---|--|
| | Brass / SS Standard Locknuts - Metric Threads | In certain applications, installing cable glands directly on enclosure or... |

Approvals



Ordering Information

Liquid Tight 45° Conduit Glands (Metric Thread)

| Cat. No. | Size | Suitable for Conduit Size | Internal Diameter (mm) | Thread Diameter D (mm) | Thread Length L (mm) | Standard Pack (Pieces) |
|---------------|------------|---------------------------|------------------------|------------------------|----------------------|------------------------|
| BBFM-07-45 | M 50 x 1.5 | 1 1/2 | 36.8 | 50 | 18 | 5 |
| BBFM-06-45 | M 40 x 1.5 | 1 1/4 | 31.8 | 40 | 15 | 5 |
| BBFM-05-45 | M 32 x 1.5 | 1 | 23.8 | 32 | 15 | 10 |
| BBFM-04-45 | M 25 x 1.5 | 3/4 | 18.5 | 25 | 15 | 25 |
| BBFM-03-45 | M 20 x 1.5 | 1/2 | 13.9 | 20 | 13 | 50 |
| BBFM-03(S)-45 | M 20 x 1.5 | 3/8 | 10.2 | 20 | 13 | 50 |
| BBFM-02-45 | M 16 x 1.5 | 3/8 | 10.2 | 16 | 11.5 | 50 |
| BBFM-08-45 | M 63 x 1.5 | 2 | 47.8 | 63 | 20 | 4 |