



## 45° Conduit Glands - PG Thread

These 45 Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

### Technical Data

Material	Nickel Plated Brass
Temperature Range	-45° C to +105° C Continuous
Threads available	Pg - Blue Insert
Protection Class	IP 67

### Accessories

Image	Cat. no.	Description
	Brass / SS Standard Locknuts - Pg Threads	In certain applications, installing cable glands directly on enclosure or...

### Approvals



## Ordering Information

### Liquid Tight 45° Conduits (Pg Thread)

Cat. No.	Size	Suitable for Conduit Size	Internal Diameter (mm)	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
BBFB-09-45	Pg 42	1 1/2	36.8	54	18	5
BBFB-08-45	Pg 36	1 1/4	31.8	47	16	5
BBFB-07-45	Pg 29	1	23.8	37	15	10
BBFB-06-45	Pg 21	3/4	18.5	29	15	25
BBFB-05-45	Pg 16	1/2	13.9	23	13	50
BBFB-04-45	Pg 13.5	3/8	10.2	21	11.5	50
BBFB-03-45	Pg 11	3/8	10.2	19	11.5	50
BBFB-10-45	Pg 48	2	47.8	59	20	4