



Straight Conduit Glands - NPT Thread

These Straight Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

Technical Data

| | |
|-------------------|---------------------------------------------------------|
| Material | Nickel Plated Brass |
| Temperature Range | -45° C to +105° C |
| Threads available | NPT - White Insert |
| Protection Class | IP 67 |
| Construction | 4 Piece Fitting (Counter Nut, Seal Ring, Ferrule, Body) |

Accessories

| Image | Cat. no. | Description |
|-------|--------------------------------------------|------------------------------------------------------------------------------|
| | Brass / SS Standard Locknuts - NPT Threads | In certain applications, installing cable glands directly on enclosure or... |

Approvals



Ordering Information

Liquid Tight Straight Conduit Glands (NPT Thread)

| Cat. No. | Size | Suitable for Conduit Size | Internal Diameter (mm) | Thread Diameter D (mm) | Thread Length L (mm) | Standard Pack (Pieces) |
|------------|------------|---------------------------|------------------------|------------------------|----------------------|------------------------|
| BBFN-02(S) | NPT 1/2" | 3/8" | 10.2 | 20.95 | 13 | 50 |
| BBFN-02 | NPT 1/2" | 1/2" | 13.9 | 20.95 | 13 | 50 |
| BBFN-03 | NPT 3/4" | 3/4" | 18.5 | 26.4 | 15 | 25 |
| BBFN-04 | NPT 1" | 1" | 23.8 | 33.2 | 15 | 10 |
| BBFN-05 | NPT 1 1/4" | 1 1/4" | 31.8 | 41.9 | 15 | 5 |
| BBFN-06 | NPT 1 1/2" | 1 1/2" | 36.8 | 47.5 | 18 | 5 |
| BBFN-07 | NPT 2" | 2" | 47.8 | 59.37 | 20 | 4 |