



Technical Data

Material	Nickel Plated Brass	
Temperature Range	-45° C to +105° C	
Threads available	NPT - White Insert	
Protection Class	IP 67	
Construction	4 Piece Fitting (Counter Nut, Seal Ring Ferrule, Body)],

Straight Conduit Glands - NPT Thread

These Straight Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

Accessories

Image	Cat. no.	Description	
00	Brass / SS Standard Locknuts - NPT Threads	In certain applications, installing cable glands directly on enclosure or	

Approvals







Ordering Information

Liquid Tight Straight Conduit Glands (NPT Thread)

Cat. No.	Size	Suitable for Conduit Size	Internal Diameter (mm)	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)			
BBFN-02(S)	NPT 1/2"	3/8"	10.2	20.95	13	50			
BBFN-02	NPT 1/2"	1/2"	13.9	20.95	13	50			
BBFN-03	NPT 3/4"	3/4"	18.5	26.4	15	25			
BBFN-04	NPT 1"	1"	23.8	33.2	15	10			
BBFN-05	NPT 1 1/4"	1 1/4"	31.8	41.9	15	5			
BBFN-06	NPT 1 1/2"	1 1/2"	36.8	47.5	18	5			
BBFN-07	NPT 2"	2"	47.8	59.37	20	4			