



Straight Conduit Glands - NPT Thread

These Straight Conduit Glands made of 4 piece fitting are designed to suit all types of liquid tight conduits. The use of nickel-plated brass guarantees high corrosion resistance. In order to maintain a common usage standard for the fittings, small adjustments on the connection sets are necessary.

Technical Data

Material	Nickel Plated Brass
Temperature Range	-45° C to +105° C
Threads available	NPT - White Insert
Protection Class	IP 67
Construction	4 Piece Fitting (Counter Nut, Seal Ring, Ferrule, Body)

Accessories

Image	Cat. no.	Description
	Brass / SS Standard Locknuts - NPT Threads	In certain applications, installing cable glands directly on enclosure or...

Approvals



Ordering Information

Liquid Tight Straight Conduit Glands (NPT Thread)

Cat. No.	Size	Suitable for Conduit Size	Internal Diameter (mm)	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
BBFN-02(S)	NPT 1/2"	3/8"	10.2	20.95	13	50
BBFN-02	NPT 1/2"	1/2"	13.9	20.95	13	50
BBFN-03	NPT 3/4"	3/4"	18.5	26.4	15	25
BBFN-04	NPT 1"	1"	23.8	33.2	15	10
BBFN-05	NPT 1 1/4"	1 1/4"	31.8	41.9	15	5
BBFN-06	NPT 1 1/2"	1 1/2"	36.8	47.5	18	5
BBFN-07	NPT 2"	2"	47.8	59.37	20	4