



## Straight Conduit Glands for AMPC Conduits - PG Thread

These fittings are exclusively designed for use with type AMPC conduits. These fittings are lightweight, easy to install and when combined with a type AMPC conduit an IP 67 cable protection system with a strong pull out strength is achieved.

## Technical Data

Material		PP (Polypropylene)
Colour		Grey
Temperature Range		-10° C to +110° C Continuous
Threads available		Pg
Protection Class		IP 54
Construction		One piece swivel fitting with integrated ferrule

## Approvals

**RoHS**

## Ordering Information

### Liquid Tight Straight Conduit Glands (Pg Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
ABFP-9	Pg 9	9	15.2	9	8.8	50
ABFP-11	Pg 11	11	18.6	9	11.1	50
ABFP-13	Pg 13	13	20.4	10	13	50
ABFP-16	Pg 16	16	22.5	10	14.8	50
ABFP-21	Pg 21	21	28.3	11	19.4	25
ABFP-29	Pg 29	29	37	12	27.9	25
ABFP-36	Pg 36	36	47	13	35.6	25
ABFP-42	Pg 42	42	54	13	41.9	25
ABFP-48	Pg 48	48	59.3	14	45.9	10