



Straight Conduit Glands for AMPC Conduits - Metric Thread

These fittings are exclusively designed for use with type AMPC conduits. These fittings are lightweight, easy to install and when combined with a type AMPC conduit an IP 67 cable protection system with a strong pull out strength is achieved.

Technical Data

Material		PP (Polypropylene)
Colour		Grey
Temperature Range		-10° C to +110° C Continuous
Threads available		Metric
Protection Class		IP 54
Construction		One piece swivel fitting with integrated ferrule

Approvals

RoHS

Ordering Information

Liquid Tight Straight Conduit Glands (Metric Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
ABFM-9	M16 X 1.5	9	16	9	8.8	50
ABFM-11	M20 X 1.5	11	20	9	11.1	50
ABFM-16	M25 X 1.5	16	25	10	14.8	50
ABFM-21	M32 X 1.5	21	32	11	19.4	25
ABFM-29	M40 X 1.5	29	40	12	27.9	25
ABFM-36	M50 X 1.5	36	50	13	35.6	25
ABFM-48	M63 X 1.5	48	63	14	45.9	10