



Straight & 90° Elbow Glands for ANMSF Conduits - NPT Thread

These fittings are designed for use with conduit types ANMSF. When used in combination with one of these conduits an IP 67 leak-tight cable protection system with a strong pull strength is achieved. They are available in sizes from NPT ½ inch to NPT2 inch in both straight and 900 fashion.

Technical Data

Material	Polyamide PA-6, V-2 , halogenfree
Colour	Grey
Temperature Range	-40° C to +120° C Continuous
Threads available	NPT
Protection Class	IP 67(Dust proof, Water tight)
Construction	Plastic fitting, consisting of 2 parts (counter nut and body)

Approvals



Ordering Information

Liquid Tight Straight Conduit Glands (NPT Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
BBFN-02A	NPT 1/2"	3/8"	20.95	14	10.9	25
BBFN-03A	NPT 1/2"	1/2"	20.95	14	14.4	25
BBFN-04A	NPT 3/4"	3/4"	26.4	16	18	10
BBFN-05A	NPT 1"	1"	33.2	16	23.9	5
BBFN-06A	NPT 1 1/4"	1 1/4"	41.9	18	30.6	5
BBFN-07A	NPT 1 1/2"	1 1/2"	47.5	19	35.4	1
BBFN-08A	NPT 2"	2"	59.37	21	47.8	1

Liquid Tight 90° Conduit Glands (NPT Thread)

Cat. No.	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Minimum Internal Bore (mm)	Standard Pack (Pieces)
BBFN-02A 90	NPT 1/2"	3/8"	20.95	14	10.9	10
BBFN-03A 90	NPT 1/2"	1/2"	20.95	14	14.4	10
BBFN-04A 90	NPT 3/4"	3/4"	26.4	16	18	10
BBFN-05A 90	NPT 1"	1"	33.2	16	23.9	5
BBFN-06A 90	NPT 1 1/4"	1 1/4"	41.9	18	30.6	5
BBFN-07A 90	NPT 1 1/2"	1 1/2"	47.5	19	35.4	1
BBFN-08A 90	NPT 2"	2"	59.37	21	47.8	1