



Polyamide Locknuts - Metric Thread

In standard industrial applications, installing cable glands directly on enclosure or equipment wall surfaces is not possible. In such situations Hexagonal Lock Nuts are used to secure cable glands. They are manufactured according to the requirement of DIN 46320. They are available in Metric thread.

Technical Data

Material	Polyamide 6 30% glass fibre reinforced
Colour	RAL 7001 (Grey) RAL 9005 (Black) RAL 7035 (L. Grey on request)
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Threads available	Metric Thread - EN 60423

Ordering Information

Metric Thread - EN 60423

Cat. No. Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BML-0S	M 12 x 1.5	5	18	100
BML-01	M 16 x 1.5	5	22	50
BML-02	M 20 x 1.5	6	26	50
BML-03	M 25 x 1.5	6	32	25
BML-04	M 32 x 1.5	7	41	25
BML-05	M 40 x 1.5	7	50	10
BML-06	M 50 x 1.5	8	60	10
BML-07	M 63 x 1.5	8	75	10
BML-08	M 75 x 2.0	15	85	10

Metric Thread - EN 60423

Cat. No. Light Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BML-1S	M 12 x 1.5	5	18	100
BML-11	M 16 x 1.5	5	22	50
BML-12	M 20 x 1.5	6	26	50
BML-13	M 25 x 1.5	6	32	25
BML-14	M 32 x 1.5	7	41	25
BML-15	M 40 x 1.5	7	50	10
BML-16	M 50 x 1.5	8	60	10
BML-17	M 63 x 1.5	8	75	10
BML-18	M 75 x 2.0	15	85	10

Metric Thread - EN 60423

Cat. No. Black	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BML-2S	M 12 x 1.5	5	18	100
BML-21	M 16 x 1.5	5	22	50
BML-22	M 20 x 1.5	6	26	50
BML-23	M 25 x 1.5	6	32	25

Metric Thread - EN 60423

Cat. No. Black	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BML-24	M 32 x 1.5	7	41	25
BML-25	M 40 x 1.5	7	50	10
BML-26	M 50 x 1.5	8	60	10
BML-27	M 63 x 1.5	8	75	10
BML-28	M 75 x 2.0	15	85	10