



Polyamide Locknuts - NPT Thread

In standard industrial applications, installing cable glands directly on enclosure or equipment wall surfaces is not possible. In such situations Hexagonal Lock Nuts are used to secure cable glands. They are manufactured according to the requirement of DIN 46320. They are available in NPT thread.

Technical Data

Material	Polyamide 6 30% glass fibre reinforced
Colour	RAL 7001 (Grey) RAL 9005 (Black) RAL 7035 (L. Grey on request)
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Threads available	NPT Thread - ANSI B 1.20.1

Ordering Information

NPT Thread - ANSI B 1.20.1

Cat. No. Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BPL-01	NPT 3/8"	5	22	50
BPL-02	NPT 1/2"	5	27	50
BPL-03	NPT 3/4"	5	33	25
BPL-04	NPT 1"	6	42	20

NPT Thread - ANSI B 1.20.1

Cat. No. Light Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BPL-11	NPT 3/8"	5	22	50
BPL-12	NPT 1/2"	5	27	50
BPL-13	NPT 3/4"	5	33	25
BPL-14	NPT 1"	6	42	20

NPT Thread - ANSI B 1.20.1

Cat. No. Black	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BPL-21	NPT 3/8"	5	22	50
BPL-22	NPT 1/2"	5	27	50
BPL-23	NPT 3/4"	5	33	25
BPL-24	NPT 1"	6	42	20