



Standard Polyamide Blind Stops - Pg Thread in Polyamide (Circular)

Blind Stops made of Polyamide 6 are used wherever threads previously cut must be closed for preventing dust, dirt and foreign matters from entering the enclosure or equipment. O rings of Neoprene should be mounted on the threaded part to get the IP 68 protection. They are also available in Hexagonal shape and longer thread size.

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black) RAL 7035 (L. Grey on request)
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Threads available	Pg Thread
Protection Class	IP 54

Ordering Information

Pg Thread in Polyamide (Circular)

Cat. No. Grey	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-01(Y)	3	12.5	6	Pg 7	100
BBS-02(Y)	3	15.2	6	Pg 9	100
BBS-03(Y)	3	18.6	6	Pg 11	50
BBS-04(Y)	3	20.4	6	Pg 13.5	50
BBS-05(Y)	3.4	22.5	6	Pg 16	50
BBS-06(Y)	4	28.3	8	Pg 21	25
BBS-07(Y)	3.2	37	8	Pg 29	25
BBS-08(Y)	3.7	47	10	Pg 36	25

Pg Thread in Polyamide (Circular)

Cat. No. Light Grey	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-11(Y)	3	12.5	6	Pg 7	100
BBS-12(Y)	3	15.2	6	Pg 9	100
BBS-13(Y)	3	18.6	6	Pg 11	50
BBS-14(Y)	3	20.4	6	Pg 13.5	50
BBS-15(Y)	3.4	22.5	6	Pg 16	50
BBS-16(Y)	4	28.3	8	Pg 21	25
BBS-17(Y)	3.2	37	8	Pg 29	25
BBS-18(Y)	3.7	47	10	Pg 36	25
BBS-19(Y)	6	54	10	Pg 42	20
BBS-20(Y)	6.5	59.3	12	Pg 48	20

Pg Thread in Polyamide (Circular)

Cat. No. Black	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-21(Y)	3	12.5	6	Pg 7	100
BBS-22(Y)	3	15.2	6	Pg 9	100
BBS-23(Y)	3	18.6	6	Pg 11	50
BBS-24(Y)	3	20.4	6	Pg 13.5	50
BBS-25(Y)	3.4	22.5	6	Pg 16	50
BBS-26(Y)	4	28.3	8	Pg 21	25
BBS-27(Y)	3.2	37	8	Pg 29	25
BBS-28(Y)	3.7	47	10	Pg 36	25