



## Standard Polyamide Blind Stops - Pg Thread in Polyamide (Circular)

Blind Stops made of Polyamide 6 are used wherever threads previously cut must be closed for preventing dust, dirt and foreign matters from entering the enclosure or equipment. O rings of Neoprene should be mounted on the threaded part to get the IP 68 protection. They are also available in Hexagonal shape and longer thread size.

### Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black) RAL 7035 (L. Grey on request)
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Threads available	Pg Thread
Protection Class	IP 54

### Ordering Information

#### Pg Thread in Polyamide (Circular)

Cat. No. Grey	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-01(Y)	3	12.5	6	Pg 7	100
BBS-02(Y)	3	15.2	6	Pg 9	100
BBS-03(Y)	3	18.6	6	Pg 11	50
BBS-04(Y)	3	20.4	6	Pg 13.5	50
BBS-05(Y)	3.4	22.5	6	Pg 16	50
BBS-06(Y)	4	28.3	8	Pg 21	25
BBS-07(Y)	3.2	37	8	Pg 29	25
BBS-08(Y)	3.7	47	10	Pg 36	25

#### Pg Thread in Polyamide (Circular)

Cat. No. Light Grey	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-11(Y)	3	12.5	6	Pg 7	100
BBS-12(Y)	3	15.2	6	Pg 9	100
BBS-13(Y)	3	18.6	6	Pg 11	50
BBS-14(Y)	3	20.4	6	Pg 13.5	50
BBS-15(Y)	3.4	22.5	6	Pg 16	50
BBS-16(Y)	4	28.3	8	Pg 21	25
BBS-17(Y)	3.2	37	8	Pg 29	25
BBS-18(Y)	3.7	47	10	Pg 36	25
BBS-19(Y)	6	54	10	Pg 42	20
BBS-20(Y)	6.5	59.3	12	Pg 48	20

**Pg Thread in Polyamide (Circular)**

Cat. No. Black	Total Height H (mm)	Thread Diameter TD (mm)	Thread Length TL (mm)	Size	Standard Pack (Pieces)
BBS-21(Y)	3	12.5	6	Pg 7	100
BBS-22(Y)	3	15.2	6	Pg 9	100
BBS-23(Y)	3	18.6	6	Pg 11	50
BBS-24(Y)	3	20.4	6	Pg 13.5	50
BBS-25(Y)	3.4	22.5	6	Pg 16	50
BBS-26(Y)	4	28.3	8	Pg 21	25
BBS-27(Y)	3.2	37	8	Pg 29	25
BBS-28(Y)	3.7	47	10	Pg 36	25