



Enlargers - Brass / Polyamide - PG Thread

These are used for threaded holes on machines or equipment housing which are too large or too small for the necessary glands.

Technical Data

Material	Brass Nickel Plated, Polyamide (On request)
Temperature Range	- 40 deg. C to +140 deg. C
Threads available	Pg
O Ring	NBR

Ordering Information

PG Thread Enlargers

Cat. No.	Thread Length TL (mm)	External Thread	Internal Thread	Size	Standard Pack (Pieces)
GBBE P36/P42	9	Pg36	Pg42	Pg36 - Pg42	5
GBBE P7/P9	5	Pg7	Pg9	Pg7 - Pg9	50
GBBE P9/P11	6	Pg9	Pg11	Pg9 - Pg11	50
GBBE P9/P13.5	6	Pg9	Pg13.5	Pg9 - Pg13.5	50
GBBE P11/P13.5	6	Pg11	Pg13.5	Pg11 - Pg13.5	50
GBBE P11/P16	6	Pg11	Pg16	Pg11 - Pg16	50
GBBE P13.5/P16	6.5	Pg13.5	Pg16	Pg13.5 - Pg16	50
GBBE P16/P21	6.5	Pg16	Pg21	Pg16 - Pg21	25
GBBE P13.5/P21	6.5	Pg13.5	Pg21	Pg13.5 - Pg21	50
GBBE P21/P29	7	Pg21	Pg29	Pg21 - Pg29	25
GBBE P29/P36	8	Pg29	Pg36	Pg29 - Pg36	10
GBBE P29/P48	8	Pg29	Pg48	Pg29 - Pg48	5