



Top Entry - with 1 Lever

These hoods are suitable for conductors which run perpendicular to the surface on which the appropriate hood and housing are mounted. The spring loaded single locking system ensures a perfect mating between the male and the female inserts while providing them with IP 66 protection.

Technical Data

Material		Powder Coated Die cast Alluminium alloy
Protection Class		IP 66
Gasket		Vinyl Nitrile Elastomer (NBR)
Voltage		For Inserts upto 500V
Thread		Pg, Metric

Ordering Information

1 Lever

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
WR06CT1 P16/B6	Pg 16	44 x 27	6B	1
WR10CT1P16/B10	Pg 16	57 x 27	10B	1
WR16CT1 P21/B16	Pg 21	77 x 27	16B	1
WR24CT1 M32/B24	M 32 x 1.5	104 x 27	24B	1

High Construction

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
W16HCT1 M25/A16W	M 25 x 1.5	66 x 16	16A	1
W16HCT1 P29/B16W	Pg 29	77 x 27	16B	1
W16HCT1 M32/B16W	M 32 x 1.5	77 x 27	16B	1
W48HCT1 P36/B48W	Pg 36	104 x 62	48B	1