



Top Entry - with 2 Lever

These hoods are suitable for conductors which run perpendicular to the surface on which the appropriate hood and housing are mounted. The spring loaded double locking system ensures a perfect mating between the male and the female inserts even if accidentally one of the locks opens up.

Technical Data

Material	Die cast Aluminium alloy
Protection Class	IP 66
Gasket	Vinyl Nitrile Elastomer (NBR)
Voltage	For Inserts upto 830V
Thread	Pg, Metric

Ordering Information

Hood with 2 Lever

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
WR10CT2P16 /B10	Pg 16	57 x 27	10B	1
WR16CT2P21 /B16	Pg 21	77 x 27	16B	1
WR16CT2M25 /B16	M 25 x 1.5	77 x 27	16B	1
WR24CT2P29 /B24	Pg 29	104 x 27	24B	1

High Construction Without Fitting

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
W16HCT2M25 x 2/B16W	M 25 x 1.5	77 x 27	16B	1
W24HCT2M32 x 2/B24W	M 32 x 1.5	104 x 27	24B	1
W24HCT2P29/B24W	Pg 29	104 x 27	24B	1
W32HCT2M32/A32W	M 32 x 1.5	66 x 40	32A	1