



### Top Entry - with 2 Lever

These hoods are suitable for conductors which run perpendicular to the surface on which the appropriate hood and housing are mounted. The spring loaded double locking system ensures a perfect mating between the male and the female inserts even if accidentally one of the locks opens up.

## Technical Data

Material		Die cast Aluminium alloy
Protection Class		IP 66
Gasket		Vinyl Nitrile Elastomer (NBR)
Voltage		For Inserts upto 830V
Thread		Pg, Metric

## Ordering Information

### Hood with 2 Lever

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
WR10CT2P16 /B10	Pg 16	57 x 27	10B	1
WR16CT2P21 /B16	Pg 21	77 x 27	16B	1
WR16CT2M25 /B16	M 25 x 1.5	77 x 27	16B	1
WR24CT2P29 /B24	Pg 29	104 x 27	24B	1

### High Construction Without Fitting

Cat. No.	Cable Gland Size	Enclosure Size (mm)	Suitable Enclosure Type	Standard Pack (Pieces)
W16HCT2M25 x 2/B16W	M 25 x 1.5	77 x 27	16B	1
W24HCT2M32 x 2/B24W	M 32 x 1.5	104 x 27	24B	1
W24HCT2P29/B24W	Pg 29	104 x 27	24B	1
W32HCT2M32/A32W	M 32 x 1.5	66 x 40	32A	1