




90° Elbow Conduit Glands - PG Thread

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg threads. The 90 configuration enables perpendicular conduit entry into the panel or equipment. These 90° Elbow Conduit Glands are available in Pg 7 to Pg 48 threads for conduit size 7 to 48

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	Pg
Protection Class	IP 67

Accessories

Image	Cat. no.	Description
	Polyamide Lock Nut	Lorem Ipsum is simply dummy text of the printing and...

Approvals



Ordering Information

Pg Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PWC-P077G	Pg 7	7	12.5	11	50
PWC-P097G	Pg 9	7	15.2	11	50
PWC-P09G	Pg 9	10	15.2	13	50
PWC-P110G	Pg 11	10	18.6	13	30
PWC-P11G	Pg 11	12	18.6	13	30
PWC-P13G	Pg 13.5	10	20.4	13	30
PWC-P132G	Pg 13.5/1	12	20.4	13	30
PWC-P136G	Pg 13.5/2	16	20.4	15	30
PWC-P162G	Pg 16	12	22.5	13	30
PWC-P16G	Pg 16	16	22.5	15	30
PWC-P163G	Pg 16	22	22.5	15	30
PWC-P21G	Pg 21	22	28.3	15	20
PWC-P29G	Pg 29	28	37	15	10
PWC-P36G	Pg 36	36	47	19	10
PWC-P48G	Pg 48	48	59.3	19	10

Pg Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PWC-P077B	Pg 7	7	12.5	11	50
PWC-P097B	Pg 9	7	15.2	11	50
PWC-P09B	Pg 9	10	15.2	13	50
PWC-P110B	Pg 11	10	18.6	13	30
PWC-P11B	Pg 11	12	18.6	13	30
PWC-P13B	Pg 13.5	10	20.4	13	30

Pg Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PWC-P132B	Pg 13.5/1	12	20.4	13	30
PWC-P136B	Pg 13.5/2	16	20.4	15	30
PWC-P162B	Pg 16	12	22.5	13	30
PWC-P16B	Pg 16	16	22.5	15	30
PWC-P163B	Pg 16	22	22.5	15	30
PWC-P21B	Pg 21	22	28.3	15	20
PWC-P29B	Pg 29	28	37	15	10
PWC-P36B	Pg 36	36	47	19	10
PWC-P48B	Pg 48	48	59.3	19	10