



90° Elbow Conduit Glands - Metric Thread

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Metric threads. The 90 configuration enables perpendicular conduit entry into the panel or equipment. These 90° Elbow Conduit Glands are available in M 12 to M 50 threads for conduit size 7 to 48

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Threads available	Metric
Protection Class	IP 67

Accessories

Image	Cat. no.	Description
	Polyamide Lock Nut	Lorem Ipsum is simply dummy text of the printing and...

Approvals



Ordering Information

Metric Thread

Cat. No. Grey	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PWC-M107G	M 12 x 1.5	7	12	11	50
PWC-M10G	M 12 x 1.5	10	12	13	50
PWC-M12G	M 16 x 1.5	12	16	13	50
PWC-M202G	M 20 x 1.5	12	20	13	50
PWC-M16G	M 20 x 1.5	16	20	13	50
PWC-M22G	M 25 x 1.5	22	25	15	30
PWC-M28G	M 32 x 1.5	28	32	15	30
PWC-M36G	M 40 x 1.5	36	40	19	10
PWC-M48G	M 50 x 1.5	48	50	19	10

Metric Thread

Cat. No. Black	Size	Suitable for Conduit Size	Thread Diameter D (mm)	Thread Length L (mm)	Standard Pack (Pieces)
PWC-M107B	M 12 x 1.5	7	12	11	50
PWC-M10B	M 12 x 1.5	10	12	13	50
PWC-M12B	M 16 x 1.5	12	16	13	50
PWC-M202B	M 20 x 1.5	12	20	13	50
PWC-M16B	M 20 x 1.5	16	20	13	50
PWC-M22B	M 25 x 1.5	22	25	15	30
PWC-M28B	M 32 x 1.5	28	32	15	30
PWC-M36B	M 40 x 1.5	36	40	19	10
PWC-M48B	M 50 x 1.5	48	50	19	10