



## Standard Polyamide Cable Glands - G Threads

These glands are liquid tight, easy to assemble and offer good strain relief with wide clamping range. The lamellar construction of glands provide an excellent grip on the cable. Cable glands with reduced clamping range are also available on request. They are manufactured according to requirement of DIN EN 62444 / 50262. These Polyamide glands are available in thread size from G 1/4" to G 1" with clamping range from 3 mm to 25 mm, also available in reduced clamping and long thread options.

### Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey), RAL 9005 (Black) RAL 7035 (L.Grey) on request
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Protection Class	IP 68-5 Bar, 30 min
Flammability	UL 94 V2
Sealing Ring	CR-Chloroprene Rubber
Attachment Thread	ANSI B 1.20.1

### Accessories

Image	Cat. no.	Description
	Polyamide Locknuts - G Thread	In standard industrial applications, installing cable glands directly on enclosure...

### Approvals



## Ordering Information

### G Threads

Cat. No. Grey	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPF-05	G 1/4"	13.16	10	15	3 - 6.5	50
BPF-01	G 3/8"	16.66	11	22	5 - 10	50
BPF-02	G 1/2"	20.96	10	24	6 - 12	50
BPF-03	G 1/2"	20.96	11	27	10 - 14	50
BPF-04	G 3/4"	26.44	12	33	13 - 18	25
BPF-05	G 1"	33.25	13	42	18 - 25	25

### G Threads

Cat. No. Light Grey	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPF-15	G 1/4"	13.16	10	15	3 - 6.5	50
BPF-11	G 3/8"	16.66	11	22	5 - 10	50
BPF-12	G 1/2"	20.96	10	24	6 - 12	50
BPF-13	G 1/2"	20.96	11	27	10 - 14	50
BPF-14	G 3/4"	26.44	12	33	13 - 18	25
BPF-15	G 1"	33.25	13	42	18 - 25	25

### G Threads

Cat. No. Black	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPF-25	G 1/4"	13.16	10	15	3 - 6.5	50
BPF-21	G 3/8"	16.66	11	22	5 - 10	50
BPF-22	G 1/2"	20.96	10	24	6 - 12	50

**G Threads**

Cat. No. Black	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPF-23	G 1/2"	20.96	11	27	10 - 14	50
BPF-24	G 3/4"	26.44	12	33	13 - 18	25
BPF-25	G 1"	33.25	13	42	18 - 25	25

**Cable Glands with Reduced Clamping Range**

Cat. No. Grey	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPFR-05	G 1/4"	13.16	10	15	2 - 5	50
BPFR-01	G 3/8"	16.66	11	22	3 - 7	50
BPFR-02	G 1/2"	20.96	10	24	5 - 9	50
BPFR-03	G 1/2"	20.96	11	27	7 - 12	50
BPFR-04	G 3/4"	26.44	12	33	9 - 16	25
BPFR-05	G 1"	33.25	13	42	12 - 20	25

**Cable Glands with Reduced Clamping Range**

Cat. No. Light Grey	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPFR-15	G 1/4"	13.16	10	15	2 - 5	50
BPFR-11	G 3/8"	16.66	11	22	3 - 7	50
BPFR-12	G 1/2"	20.96	10	24	5 - 9	50
BPFR-13	G 1/2"	20.96	11	27	7 - 12	50
BPFR-14	G 3/4"	26.44	12	33	9 - 16	25
BPFR-15	G 1"	33.25	13	42	12 - 20	25

**Cable Glands with Reduced Clamping Range**

Cat. No. Black	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BPFR-25	G 1/4"	13.16	10	15	2 - 5	50
BPFR-21	G 3/8"	16.66	11	22	3 - 7	50
BPFR-22	G 1/2"	20.96	10	24	5 - 9	50
BPFR-23	G 1/2"	20.96	11	27	7 - 12	50
BPFR-24	G 3/4"	26.44	12	33	9 - 16	25
BPFR-25	G 1"	33.25	13	42	12 - 20	25