



Standard Brass Cable Glands - NPT Thread

These metallic glands are liquid tight, offer excellent strain relief and have lameller designed plastic inserts for protection against distortion. These glands are suitable for use in machinery and equipment, measuring and controlling devices, medical equipments and many other fields where exceptional stability and safe functioning is required. Cable glands with long thread length or reduced clamping range are also available on request. Cable gland can be produced for high temperature (3000C) with silicone sealing and reduced sealing ring. These Brass cable glands are available in thread size from NPT 3/8" to NPT 1" with clamping range from 4 mm to 25 mm.

Technical Data

Material	Brass, Nickel Plated
Temperature Range	-20° C to +100° C Continuous, -40° C to +150° C Intermittent
Protection Class	IP 68-5 Bar, 30 min.
Flammability	UL 94 V2
O Ring	Perbunan (NBR) / Silicone
Sealing Ring	CR-Chloroprene Rubber
Attachment Thread	NPT-ANSI B 1.20.1
Clamping Insert	Polyamide 6

Accessories

Image	Cat. no.	Description
	Brass / SS Standard Locknuts - NPT Threads	In certain applications, installing cable glands directly on enclosure or...

Approvals



Ordering Information

NPT Thread

Cat. No.	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
BNBC-01	NPT 3/8"	17.15	11.5	17	4 - 8	50
BNBC-01S	NPT 3/8"	17.15	11.5	20	5 - 10	50
BNBC-02	NPT 1/2"	21.34	13	22	6 - 12	50
BNBC-02S	NPT 1/2"	21.34	13	24	10 - 14	50
BNBC-03	NPT 3/4"	26.67	13	30	13 - 18	25
BNBC-04	NPT 1"	33.4	13	40	18 - 25	10
BNBC-05	NPT 1 1/4"	42.16	25.6	50	22 - 32	10
BNBC-06	NPT 1 1/2"	48.26	26	58	30 - 38	10
BNBC-07	NPT 2"	60.33	27	64	34 - 44	10