



Explosion Proof Polyamide Blind Stops

Blind Stops made of Brass are used wherever threads previously cut must be closed for preventing dust, dirt and foreign matters from entering the enclosure or equipment. These blind stops are produced in accordance with EN 60079-7:2015. Suitable for use in hazardous areas such as mining and petrochemical industry and carries ATEX directives.

Technical Data

Material	Polyamide 6
Colour	RAL 9005 (Black)
Temperature Range	40° C to +80° C
Protection Class	IP 68 - 5 Bar, 30 Min
O Ring	Chloroprene
Certificate No	IMQ 13 ATEX 010 X
Equipment Marking	Ex II 2GD Ex eb IIC Gb / Ex tb IIC Db
Suitable for use in	Group II Gas Group IIC Zone1/Zone2 Group III Dust Group IIIC Zone21/Zone22

Approvals



Ordering Information

Metric Thread

Cat. No.	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Total Height H (mm)	Standard Pack (Pieces)
TP-X02	M 12 x 1.5	12	10	15	15	100
TP-X01	M 16 x 1.5	16	11	19	15.3	50
TP-X1	M 20 x 1.5	20	11	23	17	50
TP-X2	M 25 x 1.5	25	10	28	15.8	50
TP-X3	M 32 x 1.5	32	15.5	36	22.8	25
TP-X4	M 40 x 1.5	40	18	46	26.5	10
TP-X5	M 50 x 1.5	50	18	55	27.5	10
TP-X6	M 63 x 1.5	63	18	69	27.5	10
TP-X02	M 12 x 1.5	12	10	15	15	100
TP-X01	M 16 x 1.5	16	11	19	15.3	50
TP-X1	M 20 x 1.5	20	11	23	17	50
TP-X2	M 25 x 1.5	25	10	28	15.8	50
TP-X3	M 32 x 1.5	32	15.5	36	22.8	25
TP-X4	M 40 x 1.5	40	18	46	26.5	10
TP-X5	M 50 x 1.5	50	18	55	27.5	10
TP-X6	M 63 x 1.5	63	18	69	27.5	10