



### Explosion Proof Drain Plugs

Explosion Proof Drain Plugs effectively drains moisture out of an enclosure. It prevents damages, such as condensation water and allows the air inside the enclosure to breathe with the surrounding atmosphere.

### Technical Data

Material	Brass Nickel Plated,Stainless Steel 316L
Temperature Range	Ex e/tb -60° C to +85° C
Protection Class	IP 66 (EN60529)
Membrane Material	Bronze
O Ring	Silicone
Equipment Marking	Ex II 2GD Ex eb IIC Gb Ex tb IIIC Db
Suitable for use in	Group II Gas Group IIC Zone1/Zone2 Group III Dust
Certificate Number	IMQ 13 ATEX 030 X

### Approvals



### Ordering Information

#### Metric Thread - Drain Plug

Cat. No.	Size	Thread Length L (mm)	Spanner Size (mm)	Total Height H (mm)	Outer Diameter D (mm)
BDRV-1M	M 20 x 1.5	16	25	16	27.5
BDRV-2M	M 25 x 1.5	16	30	16	33

#### NPT Thread - Drain Plug

Cat. No.	Size	Thread Length L (mm)	Spanner Size (mm)	Total Height H (mm)	Outer Diameter D (mm)
BDRV-1N	NPT 1/2"	16	25	16	27.5
BDRV-2N	NPT 3/4"	16	30	16	33

#### Special Lock Nuts for drain plugs

Cat. No.	Size	Thread Length L (mm)	Total Height H (mm)	Outer Diameter D (mm)
BDRL-03	M20 X 1.5	25	5	27.5
BDRL-04	M25 X 1.5	30	5	33
BDRLN-03	NPT 1/2"	25	5	27.5
BDRLN-04	NPT 3/4"	30	5	33