



Triples Seal Standard Brass & SS Cable Glands - NPT Thread

These Glands are produced in accordance to EN 60079-7:2015. Because of triple seal they have wide clamping range they are used in mobile offshore, marine application, chemical & petro chemical industry.

Technical Data

Material	Brass Nickel Plated (MB / NB Series) Stainless Steel 316L (MX / NX Series)
Temperature Range	Chloroprene Ex d/tb -40° C to +80° C Ex e/tb -40° C to +80° C Silicon Ex d/tb -60° C to +80° C Ex e/tb -60° C to +140° C
Threads available	Metric, NPT, (Pg available on request)
Protection Class	IP 68 - 5 Bar, 30 Min
O Ring	Chloroprene / Silicon
Certificate No	IMQ 13 ATEX 018 X
Equipment Marking	Ex II 2GD Ex eb IIC Gb Ex tb IIIC Db
Suitable for use in	Group II Gas Group IIC Zone1/Zone2 Group III Dust Group IIIC Zone21/Zone22
Sealing Ring	Chloroprene / Silicon

Approvals



Ordering Information

NPT Thread

Cat. No.	Size	Thread Diameter D (mm)	Thread Length L (mm)	Spanner Size (mm)	Clamping Range (mm)	Standard Pack (Pieces)
EBU01NB	NPT 3/8"	17.15	16	22	4.0 - 12	50
EBU1NB	NPT 1/2"	21.34	16	22	4.0 - 12	50
EBU12NB	NPT 1/2"	21.34	16	28	10.0 - 16.0	50
EBU2NB	NPT 3/4"	26.67	16	28	10.0 - 18.0	25
EBU23NB	NPT 3/4"	26.67	16	35	14.0 - 20.0	25
EBU3NB	NPT 1"	33.4	16	35	14.0 - 24.0	20
EBU34NB	NPT 1"	33.4	16	45	22.0 - 28.0	20
EBU4NB	NPT 1 1/4"	42.16	18	45	22.0 - 32.0	10
EBU45NB	NPT 1 1/4"	42.16	18	50	26.0 - 34.0	10
EBU5NB	NPT 1 1/2"	48.26	18	55 / 50	26.0 - 35.0	10
EBU56NB	NPT 1 1/2"	48.26	18	55 / 58	35.0 - 44.0	10
EBU6NB	NPT 2"	60.33	18	68 / 58	35.0 - 45.0	5
EBU67NB	NPT 2"	60.33	18	75 / 80	46.0 - 56.0	5
EBU7NB	NPT 2 1/2"	73.03	20	80	46.0 - 62.0	2
EBU78NB	NPT 2 1/2"	73.03	20	95	60.0 - 69.0	2
EBU8NB	NPT 3"	88.9	20	95	60.0 - 75.0	2
EBU810NB	NPT 3"	88.9	20	105	75.0 - 82.0	2
EBU10NB	NPT 4"	114.3	20	105	75.0 - 85.0	1
EBU11NB	NPT 4"	114.3	20	150	85.0 - 95.0	1