



Blind Stops Brass & SS - PG Thread

Blind Stops made of Brass are used wherever threads previously cut must be closed for preventing dust, dirt and foreign matters from entering the enclosure or equipment. These blind stops are produced in accordance with EN 60079-7:2015.

Technical Data

Material	Brass Nickel Plated (MB Series) Stainless Steel 316L (MX Series)
Temperature Range	Chloroprene -40° C to +100° C Silicon -60° C to +130° C
Threads available	Metric, NPT, (Pg available on request)
Protection Class	IP 68 - 5 Bar, 30 Min
O Ring	Chloroprene / Silicon
Certificate No	CESI 13 ATEX 066 X
Equipment Marking	Ex II 2GD Ex eb IIC Gb Ex tb IIIC Db
Suitable for use in	Group II Gas Group IIC Zone1/Zone2 Group III Dust Group IIIC Zone21/Zone22
Sealing Ring	Chloroprene / Silicon

Approvals



Ordering Information

PG Thread

Cat. No.	Size	Thread Diameter D (mm)	Thread Length L (mm)	Total Height H (mm)	Standard Pack (Pieces)
B-TS2PB	Pg 9	15.2	16.5	22	25
B-TS3PB	Pg 11	18.6	16.5	22	20
B-TS4PB	Pg 13.5	20.4	16.5	22	20
B-TS5PB	Pg 16	22.5	16.5	22	10
B-TS6PB	Pg 21	28.3	17	22	10
B-TS7PB	Pg 29	37	17	22	10
B-TS8PB	Pg 36	47	17	22	5
B-TS9PB	Pg 42	54	17	22	5
B-TS10PB	Pg 48	59.3	17	22	5