



### Blind Stops Brass & SS - Metric Thread

Blind Stops made of Brass are used wherever threads previously cut must be closed for preventing dust, dirt and foreign matters from entering the enclosure or equipment. These blind stops are produced in accordance with EN 60079-7:2015.

### Technical Data

Material	Brass Nickel Plated (MB Series) Stainless Steel 316L (MX Series)
Temperature Range	Chloroprene -40° C to +100° C Silicon -60° C to +130° C
Threads available	Metric, NPT, (Pg available on request)
Protection Class	IP 68 - 5 Bar, 30 Min
O Ring	Chloroprene / Silicon
Certificate No	CESI 13 ATEX 066 X
Equipment Marking	Ex II 2GD Ex eb IIC Gb Ex tb IIIC Db
Suitable for use in	Group II Gas Group IIC Zone1/Zone2 Group III Dust Group IIIC Zone21/Zone22
Sealing Ring	Chloroprene / Silicon

### Approvals



### Ordering Information

#### Metric Thread

Cat. No.	Size	Thread Diameter D (mm)	Thread Length L (mm)	Total Height H (mm)	Standard Pack (Pieces)
B-TS01MB	M 16 x 1.5	16	15.5	21	25
B-TS1MB	M 20 x 1.5	20	15.5	21	25
B-TS2MB	M 25 x 1.5	25	15.5	21	20
B-TS3MB	M 32 x 1.5	32	15.5	21	20
B-TS4MB	M 40 x 1.5	40	17.5	23	10
B-TS5MB	M 50 x 1.5	50	17.5	23	10
B-TS6MB	M 63 x 1.5	63	17.5	23	10
B-TS7MB	M 75 x 1.5	75	20	25	5
B-TS8MB	M 90 x 1.5	90	20	25	5
B-TS10MB	M 110 x 1.5	110	20	25	5