



## Polyamide Locknuts - Pg Thread

In standard industrial applications, installing cable glands directly on enclosure or equipment wall surfaces is not possible. In such situations Hexagonal Lock Nuts are used to secure cable glands. They are manufactured according to the requirement of DIN 46320. They are available in PG thread.

## Technical Data

Material	Polyamide 6 30% glass fibre reinforced
Colour	RAL 7001 (Grey) RAL 9005 (Black) RAL 7035 (L. Grey on request)
Temperature Range	-20° C to +100°C Continuous, -30°C to +150°C Intermittent
Threads available	Pg Thread - DIN 40430

## Ordering Information

### Pg Thread - DIN 40430

Cat. No. Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BL-01	Pg 7	5	19	50
BL-02	Pg 9	5	22	50
BL-03	Pg 11	5	24	50
BL-04	Pg 13.5	6	27	50
BL-05	Pg 16	6	30	50
BL-06	Pg 21	7	36	25
BL-07	Pg 29	7	46	20
BL-08	Pg 36	8	60	10
BL-09	Pg 42	8	65	10
BL-10	Pg 48	8	70	10

### Pg Thread - DIN 40430

Cat. No. Light Grey	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BL-11	Pg 7	5	19	50
BL-12	Pg 9	5	22	50
BL-13	Pg 11	5	24	50
BL-14	Pg 13.5	6	27	50
BL-15	Pg 16	6	30	50
BL-16	Pg 21	7	36	25
BL-17	Pg 29	7	46	20
BL-18	Pg 36	8	60	10
BL-19	Pg 42	8	65	10
BL-20	Pg 48	8	70	10

### Pg Thread - DIN 40430

Cat. No. Black	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BL-21	Pg 7	5	19	50
BL-22	Pg 9	5	22	50

**Pg Thread - DIN 40430**

Cat. No. Black	For Cable Gland Size	Height (mm)	Spanner Size (mm)	Standard Pack (Pieces)
BL-23	Pg 11	5	24	50
BL-24	Pg 13.5	6	27	50
BL-25	Pg 16	6	30	50
BL-26	Pg 21	7	36	25
BL-27	Pg 29	7	46	20
BL-28	Pg 36	8	60	10
BL-29	Pg 42	8	65	10
BL-30	Pg 48	8	70	10