



Metal Drain Plugs - Metric Thread

Balances pressure differences between the inner housing and the outside environment. It prevents damages according to pressure differences and prevents the formation of water condensation in tightly-sealed standard housings. They are available in Metric thread.

Technical Data

| Material | Brass Nickel Plated / Stainless Steel |
|-------------------|---------------------------------------------|
| Temperature Range | -60° C to +85°C |
| Protection Class | IP 68 - 5 Bar, 30 min IP 66 - 5 Bar, 30 min |
| O Ring | Silicon |
| Bushing | Bronze |

Accessories

| Image | Cat. no. | Description | | |
|-------|------------------------------------------|-------------------------------------------------------------------------|--|--|
| | Metal Drain Plugs - Special Lock Nuts | Balances pressure differences between the inner housing and the outside | | |

Product Drawing



Ordering Information

Metric Thread - Drain Plug

| Cat. No. | Spanner Size (mm) | Total Height H (mm) | Thread Length TL (mm) | Size | Outer Diameter D (mm) | Standard Pack (Pieces) |
|----------|-------------------|---------------------|-----------------------|------------|-----------------------|------------------------|
| IBDRV-1M | 25 | 16 | 15 | M 20 x 1.5 | 27.5 | 10 |
| IBDRV-2M | 30 | 16 | 15 | M 25 x 1.5 | 33 | 10 |

CONTROLWELL INDIA PVT.LTD | D7,Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India-421204 Tel.: +91 251 7120 600 / 6762 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com