



# Metal Drain Plugs - NPT Thread

Balances pressure differences between the inner housing and the outside environment. It prevents damages according to pressure differences and prevents the formation of water condensation in tightly-sealed standard housings. They are available NPT thread.

#### **Technical Data**

Material	Brass Nickel Plated / Stainless Steel
Temperature Range	-60° C to +85°C
Protection Class	IP 68 - 5 Bar, 30 min IP 66 - 5 Bar, 30 min
O Ring	Silicon
Bushing	Bronze

#### **Accessories**

Image	Cat. no.	Description		
	Metal Drain Plugs - Special Lock Nuts	Balances pressure differences between the inner housing and the outside		

# **Product Drawing**



# **Ordering Information**

#### **NPT Thread - Drain Plug**

Cat. No.	Spanner Size (mm)	Total Height H (mm)	Thread Length TL (mm)	Size	Outer Diameter D (mm)	Standard Pack (Pieces)
IBDRV-1N	25	16	16	NPT 1/2"	27.5	10
IBDRV-2N	30	16	16	NPT 3/4"	33	10

CONTROLWELL INDIA PVT.LTD | D7,Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India-421204 Tel.: +91 251 7120 600 / 6762 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com