




Straight Conduit Glands With Flange

These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection. These connectors are available with mounting holes for fixing on the panel or equipment surface.

Technical Data

Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67

Product Drawing



Ordering Information

Cat. No. Grey	Suitable for Conduit Size	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (Pieces)
PNOC-12G	12	-	36.5	5.5	46	32	50
PNOC-16G	16	-	36.5	5.5	46	32	50
PNOC-22G	22	31	54.8	6.5	64.8	45	30
PNOC-28G	28	31	54.8	6.5	64.8	45	20
PNOC-36G	36	31	72.6	6.5	86.6	64	10
PNOC-48G	48	30.5	72.6	6.5	86.6	78	10

Cat. No. Black	Suitable for Conduit Size	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (Pieces)
PNOC-12B	12	-	36.5	5.5	46	32	50
PNOC-16B	16	-	36.5	5.5	46	32	50
PNOC-22B	22	31	54.8	6.5	64.8	45	30
PNOC-28B	28	31	54.8	6.5	64.8	45	20
PNOC-36B	36	31	72.6	6.5	86.6	64	10
PNOC-48B	48	30.5	72.6	6.5	86.6	78	10