




Modified Polyamide Flexible Conduits Slitted / Unslitted - SPAER

Modified Polyamide Flexible Conduits are made of self-extinguishing Polyamide 6. They are flexible, UV resistant, and halogen-free and have a small bending radius. They offer good impact resistance and are suitable for various applications such as vehicle industries, body section and chassis etc. These Conduits offer IP 67 protection in combination with Conduit Glands.

Technical Data

Material	Modified Polyamide 6
Temperature Range	-40° C to +150° C Continuous, +175° C Intermittent
Protection Class	IP 67
Tensile Strength	250 N
Impact Strength	1 J
Compression Resistance	320 N

Accessories

Image	Cat. no.	Description
	Mounting Clips	Mounting Clips are used for supporting conduits. These clips are...

Approvals

RoHS

Ordering Information

Cat. No. Slitted	Inner Diameter (mm)	Outer Diameter (mm)	Size	Standard Pack (meters)
SPAERS-37	36	42.4	NW-37	25
SPAERS-29	29	34.5	NW-29	25
SPAERS-26	25.8	31.2	NW-26	25
SPAERS-23	23.2	28.3	NW-23	50
SPAERS-22	21.3	25.4	NW-22	50
SPAERS-17	16.6	21.2	NW-17	50
SPAERS-13	12.7	15.8	NW-13	50
SPAERS-12	12.2	15.7	NW-12	50
SPAERS-10	9.9	13	NW-10	50
SPAERS-7.5	6.7	10	NW-7.5	50
SPAERS-4.5	5	7.1	NW4.5	100
SPAERS-50	37.7	54	NW-50	25

Cat. No. Unslitted	Inner Diameter (mm)	Outer Diameter (mm)	Size	Standard Pack (meters)
SPAER-50	37.7	54	NW-50	25
SPAER-37	36	42.4	NW-37	25
SPAER-29	29	34.5	NW-29	25
SPAER-26	25.8	31.2	NW-26	25
SPAER-23	23.2	28.3	NW-23	50
SPAER-22	21.3	25.4	NW-22	50
SPAER-17	16.6	21.2	NW-17	50
SPAER-13	12.7	15.8	NW-13	50
SPAER-12	12.2	15.7	NW-12	50
SPAER-10	9.9	13	NW-10	50
SPAER-7.5	6.7	10	NW-7.5	50

Cat. No. Unslitted	Inner Diameter (mm)	Outer Diameter (mm)	Size	Standard Pack (meters)
SPAER-4.5	5	7.1	NW4.5	100