




Twin Slitted Conduits (Closable Profile)

Twin Slitted PA6, UV resistant conduits are used in applications where intermediate repair is expected. When wires or cables are to be replaced for repair work these conduits are the perfect solution. They are used in medium and heavy machines, computer installations, ship & train building, packaging machines and automotive industry.

Technical Data

Material	Polyamide 6
Temperature Range	-40° C to +120° C Continuous, +150° C Intermittent
Protection Class	IP 54
Tensile Strength	500 N
Impact Strength	2 J
Compression Resistance	750 N

Accessories

Image	Cat. no.	Description
	Mounting Clips	Mounting Clips are used for supporting conduits. These clips are...

Approvals

RoHS

Ordering Information

Cat. No.	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius R (mm)	Size	Standard Pack (meters)
STSC-7.5	5.6	10.3	25	NW-7.5	50
STSC-10	8.5	13.3	33	NW-10	50
STSC-13	11	16	35	NW-13	50
STSC-16	13	19	42	NW-16	50
STSC-17	15.5	21.5	45	NW-17	50
STSC-22	19.1	25.6	55	NW-22	50
STSC-23	21.9	28.5	68	NW-23	50
STSC-26	24	31.7	80	NW-26	25
STSC-29	27.2	35	120	NW-29	25
STSC-37	32	42.5	145	NW-37	25
STSC-50	43.9	53.9	150	NW-50	25
STSC-70	62.2	79	150	NW-70	10